



REV	BY	DATE




**Gared Holdings, LLC**  
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**MAT HOIST SAFETY STRAP PACKAGE**

DRAWN	MJP	DATE	11/1/2022	DATE ISSUED	11/1/2022
APPROVED		DATE			

FILE LOC. Q:\Inventor Files\Specification Files\09\_Accessories

SIZE	SCALE	SHT. NO.	PART NO.	REV
<b>A</b>	NONE	1 OF 2	<b>155655941 R002</b>	



## MODEL 155655941

### **MAT HOIST SAFETY STRAP PACKAGE**

This package is designed to prevent free-fall of mat slings due to cable or hoist gearbox failure. A sudden surge of speed due to failure shall instantly lock and hold the load bar in any position. This unit sets by inertial force for immediate and positive setting.

The two pair of “Safstops”, model 1100, are attached to the mat storage system I-Beam with a pair of high strength mounting brackets. The four “Safstops” have 2" [51 mm] wide nylon belt each with a tensile strength of 6000 lbs [2722 kg] and can extend 35 feet [10.7 m]. The belts are attached to the load bar using buckle connections.

The “Safstops” have automatic spring-loaded resets and do not require electricity to operate. Each lock by inertial force for immediate and positive setting. The locking mechanism is contained within a cast aluminum housing.

The Mat Hoist Safety Strap Package is recommended for any mat hoist raised over seating or high activity area.

#### **CAUTION:**

**Mat Storage System Lock is rated to catch a 4000 lbs. falling load. This does not ensure that other components, such as building structure will withstand thrust load.**