



SCOREBOARD SPECIFICATIONS

MODEL GS-265

Lead your team with this arena style 4-sided basketball scoreboard! Large 15" & 9" high super-bright 100,000-hour rated LED numerals are the largest with the widest viewing angle in the industry and are visible over 300 feet. The 22-gauge galvanized steel cabinet with powder-coat finish means your scoreboard is the most durable on the market and will look brand new for many years! Scoreboard package includes: operator's keyboard, junction box cover (cable models only), and a complete installation/operation service manual and warranty details on the CD shipped with the scoreboard.

OVERALL DIMENSIONS

13'4" L x 3' W x 8" D shipped in four (4) sections, hardware boxed separately.

WEIGHT

Hanging weight: 1800 lbs.
Shipping weight: 2300 lbs.

CONSTRUCTION

22-gauge galvanized steel cabinet with powder coat finish for strength, durability, and lasting appearance

POWER REQUIREMENTS

Scoreboard:

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

Controller:

Standard LCD controller powered by 12V DC Adapter or an optional internal battery

SCORING INFORMATION DISPLAYED

HOME and GUEST: 3-digit displays, 0-199

CLOCK: 4-digit displays, counts up or down, 99:59-00:00 or 00:00-99:59

PERIOD: 1-digit display, 1-9

BONUS: 4 – 2.0" dot indicator

POSSESSION: 2 – 2.0" arrow indicator

CAPTIONS

HOME and GUEST: 8" H

PERIOD: 4" H

POSS: 3" H

CLOCK COLON: 2" H

BONUS: 4" H

Polymeric Calendared Vinyl Lettering

CLOCK Displays

15" H digits, 160° visibility, amber, 100,000 hour-rated, indoor super-bright LED (light emitting diode) displays

HOME and GUEST Displays

15" H digits, 160° visibility, red, 100,000 hour-rated, indoor super-bright LED (light emitting diode) displays

PERIOD Display

9" H digits, 160° visibility, green, 100,000 hour-rated, indoor super-bright LED (light emitting diode) display

BONUS and POSSESSION Indicators

2.0" LED dot/arrow indicators, 160° visibility, red, 100,000 hour-rated, indoor super-bright LED (light emitting diode) displays

APPROVALS

ETL/CSA listed

Scoreboard: Meets all FCC Class A requirements.

2.4 GHz wireless transmitter: FCC Part 15 certified.

2.4 GHz wireless receiver: Meets all FCC Part 15 requirements.

WARRANTY

This product is warranted against defects in materials and workmanship for the period specified in the warranty from the date of invoice.

INSTALLATION

This model may be wall mounted or suspended from the ceiling.

Support structure and mounting hardware supplied by installer/others

SCOREBOARD CONTROLLER

Dimensions: 14" L x 7" W x 2.5" H

Weight: 2.10 lbs.

The keyboard controller available with this scoreboard is microprocessor-controlled, molded of high-impact ABS plastic, has a tactile membrane keypad. Options include 2.4 GHz wireless control and internal battery pack with automatic battery charger.

Cable-Controlled System (standard) Includes:

- (1) Keyboard controller
- (3) BASKETBALL keypad inserts
- (1) Junction box cover with receptacle (to be installed at scorekeeper's location)
- (1) 20-ft. signal cable (used to connect the keyboard to the junction box receptacle)
- (1) Project-specific length of 4 wire twisted pair, shielded control cable

2.4 GHz Wireless System (optional) Includes:

- (1) Universal LCD keyboard controller
- (3) BASKETBALL keypad inserts
- (1) 12-volt DC wall transformer
- (1) 2.4 GHz transmitter (connects to keyboard controller via supplied interface cable)
- (1) 2.4 GHz receiver (connects to the scoreboard, eliminating control cable and junction box installation)

OPTIONS

(1) Wireless Remote Control System (If you wish to run two wireless scoreboards in synchronization with one wireless control keyboard, you will need to order a wireless remote control system for each scoreboard. It must be factory installed.)

- (1) Wireless Remote Control Battery Option (charger included)
- (1) Message Center
- (1) Electronic Team Names
- (1) Sponsor Panels
- (1) Controller Carry Case