



FRONT VIEW

REAR VIEW

SECTION A-A

MATERIAL IS 1/2" THICK TEMPERED GLASS WITH STEEL FRAME
 FINISH IS GRAY POWDER COAT ON BRACKETS AND PLATES..

| | | |
|-----|----|------|
| REV | BY | DATE |
| | | |

PSS
PERFORMANCE
SPORTS SYSTEMS

GARED

Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

RECTANGLE GLASS BOARD. 42" X 54"

| | | | | |
|----------|--------|------|-----------|-------------|
| DRAWN | CROSBY | DATE | 1/16/2015 | DATE ISSUED |
| APPROVED | | DATE | | |

FILE LOC. Q:\Inventor Files\Specification Files\07_Backboards

| | | | | |
|------|-------|----------|----------|-----|
| SIZE | SCALE | SHT. NO. | PART NO. | REV |
| A | | 1 OF 2 | 3050 | |



MODEL 3050

STEEL FRAME 54" X 42" RECTANGULAR GLASS BACKBOARD

The 3050 backboard shall be fabricated with heavy steel frame constructed of formed steel angles and fastened together with heavy gauge steel mounting plates to reinforce corners. Entire frame and components shall be powder coated with a durable neutral gray finish. Acrylic cushioning tape shall be used between steel mounting plate and glass to protect board against possible breakage.

Mounting brackets shall be positioned at 36" vertical and 45" horizontal centers for mounting backboard.

Glass shall be ½" in thickness and is fully tempered with the white target lines permanently fused onto the surface. 12mm glass will not be considered equal to ½" glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full ½" glass. Vinyl shock absorbing material shall insulate the glass from the frame. Goal mounting holes shall be on standard 5" horizontal and 4" vertical centers.

ACCESSORIES

GOALS

See Goal-Board Matrix specification sheet for goal compatibility.