





Gared Holdings, LLC 9200 E. 146th St. Noblesville, IN 46060 THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

## BACKBOARD, 36" X 48" ACRYLIC

DRAWN CROSBY			7/30/2019		DATE ISSUED	
APPROVED			TE			
FILE LOC. Q:\Inventor Files\Specification Files\07_Backboards						
SIZE	SCALE	SHT. NO.	PART NO.			REV
ll A		1 OF 2		BB	48A38	C





## MODEL BB48A38

## STEEL FRAME 48" X 36" RECTANGULAR ACRYLIC BACKBOARD

Backboard shall be constructed of a unitized welded tubular frame utilizing heavy wall ¾ x 1.5" rectangular steel tubing. Frame shall include two vertical struts on 20 inch centers with holes for mounting to support structure. Design shall provide a reinforced goal mounting area to allow for direct mounting of goal, board, and structure. Direct mounting design shall have integral holes to allow permanent attachment of board to post and allow for goal replacement without removing the board.

Backboard shall be designed for use with residential adjustable units, gooseneck posts, and straight arm posts.

Backboard surface shall be constructed of 3/8" thick clear acrylic treated for UV protection, and abrasion resistance. Goal mounting holes shall be on standard 5" horizontal and 5" vertical centers.

Board frame shall be powder coated separately with a flat black weather resistant finish before being assembled.

## **GOALS**

See Goal-Board Matrix specification sheet for goal compatibility.