



A	9/22/22	MJP
REV	BY	DATE



  
**GARED**
  
 Gared Holdings, LLC
   
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**MASTER VOLLEYBALL SYSTEM - 2 COURT**

DRAWN	MJP	DATE	9/22/2022	DATE ISSUED	9/22/2022
APPROVED		DATE			

FILE LOC. VAULT\Inventor Files\Specification Files\

SIZE	SCALE	SHT. NO.	PART NO.	REV
A		1 OF 2	7302	A



## **MODEL 7203**

### **TWO COURT MASTER VOLLEYBALL SYSTEM**

#### **RECOMMENDED APPLICATION**

Top quality unit for use in facilities requiring product for multi-use functions. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

#### **FLOOR SLEEVES AND COVER PLATES**

Please refer to attached specification

#### **UPRIGHTS**

System shall be supplied with one winch post, one center winch post, and one end post. Upright posts shall be 6063-T6 aluminum, 4" Diameter, 9'-6" length, post with a weight of 25 lbs. Finish shall be gray anodized. Upright posts shall be removable type with sleeves and covers and permanent fixture to the floor. Net heights shall be achieved by sliding aluminum adjustable rails to desired net height and locking rails in place with wedge type locking mechanism. Adjustable rails shall slide the full length of the post. Upright posts shall have high impact plastic caps on ends of the posts for floor protection.

#### **NET TENSIONER (WINCH)**

The net tensioner shall incorporate a heavy duty, self-locking worm gear mechanism. A high tensile nylon strap will be used with the winch to achieve required net tension.

#### **NET**

Net features include 5/8" [16 mm] diameter fiberglass dowel and 4" [102 mm] square black nylon mesh (250 lbs [113 Kg] tensile strength) for excellent performance and durability. Free floating net along 5/32" [4.0 mm] diameter steel 7 x 19 cable (2,000 lbs [907 Kg] minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with padded metallic clips are used to secure net in place. Net shall be 32' [9.75 m] length and 39" [.99 m] width. Net perimeter shall have a 2" [51 mm] wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition volleyball.

#### **UPRIGHT PADS**

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

#### **NET ANTENNA AND TAPE**

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

#### **AVAILABLE OPTIONS**

Referee Stand with optional padding  
Storage Cart