



7200 & 7205 COLLEGIATE VOLLEYBALL SYSTEM

F	ERD	08-01-23
E	MJP	9/16/22
D	MJP	03/15/22
C	RWP	06/04/08
B	ATS	04/22/05
A	MJB	12/17/03
REV	BY	DATE



Gared Performance Sports Systems
 9200 East 146th Street, Suite A
 Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED PERFORMANCE SPORTS SYSTEMS IS STRICTLY PROHIBITED.

COLLEGIATE ONE COURT VB SYS

DRAWN MJP	DATE 3/15/2022	DATE ISSUED 3/15/2022
APPROVED	DATE	

SIZE A	SCALE	SHT. NO. 1 OF 2	PART NO. 7200	REV F
------------------	-------	--------------------	-------------------------	-----------------



**PERFORMANCE
SPORTS SYSTEMS**

MODEL 7200

COLLEGIATE VOLLEYBALL SYSTEM

RECOMMENDED APPLICATION

Top quality unit for use in facilities requiring product for multi-use functions. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

FLOOR SLEEVES AND COVER PLATES

Please refer to attached specification (cover plates not included in the 7200SCS system)

UPRIGHTS

Upright posts shall be 6063-T6 aluminum, 4" Diameter, 9'-6" length, post with a weight of 25 lbs. Finish shall be gray anodized. Upright posts shall be removable type with sleeves and covers and permanent fixture to the floor. Net heights shall be achieved by sliding aluminum adjustable rails to desired net height and locking rails in place with wedge type locking mechanism. Adjustable rails shall slide the full length of the post. Upright posts shall have high impact plastic caps on ends of the posts for floor protection.

NET TENSIONER (WINCH)

The net tensioner shall incorporate a heavy duty, self-locking worm gear winch. A high tensile nylon strap will be used with the winch to achieve required net tension.

NET

(Net not included in the 7200SCS system) Net features include 5/8" [16 mm] diameter fiberglass dowel and 4" [102 mm] square black nylon mesh (250 lbs [113 Kg] tensile strength) for excellent performance and durability. Free floating net along 5/32" [4.0 mm] diameter steel 7 x 19 cable (2,000 lbs [907 Kg] minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with padded metallic clips are used to secure net in place. Net shall be 32' [9.75 m] length and 39" [.99 m] width. Net perimeter shall have a 2" [51 mm] wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition volleyball.

UPRIGHT PADS

(Upright pads not included in the 7200SCS system) Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

NET ANTENNA AND TAPE

(Net antenna and tape not included in the 7200SCS system) Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

AVAILABLE OPTIONS

Center Post Uprights for multi-court applications
Referee Stand with optional padding
Storage Cart

Subject to design change and current manufacturing practices.
Revised Apr. 24, 2014 ©2008 Gared Performance Sports Systems, LLC