



CLIMBER MAY BE MADE REMOVABLE BY ALLOWING ROOM UNDER BOLT AND ELIMINATING THE FLAT WASHER.

78.00" [1.98 m] TO FLOOR (RECOMMENDED)

**GRID CLIMBER**

REVISION		
REV.	DATE	BY
A	12/17/03	MJB
B	06/12/08	RWP

**Gared Holdings, LLC**  
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**GRID CLIMBER**

DRAWN	CONNERLEY	DATE	05/08/03	MATERIAL	N/A
APPROVED	JJC	DATE	05/08/03	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	106
SIZE	SCALE	SHT. NO.	PART NO.	REV	
<b>A</b>	NOTED	1 OF 1	<b>106</b>	<b>B</b>	



**MODEL 106**  
**GRID CLIMBER**

Grid climber support frame shall be constructed with 15/16" [33.27 mm] diameter heavy wall tubing. Support frame shall be fastened to 2 x 6 wood boards sealed and varnished that are mounted to the wall on 31 5/16" [795.34 mm] centers. Grid rungs shall be 1.0" [25.4 mm] diameter steel tubing.

**Hardware for attachment to wall not included.**

Subject to design change and current manufacturing practices.  
Revised April 4, 2008 ©2008 Gared Holdings, LLC