







Gared Holdings, LLC 9200 E. 146th St. Noblesville, IN 46060 THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

RECTANGULAR MOLDED FIBERGLASS BACKBOARD

DRAWN	CONNE	RLEY	DATE	04/01/09 MATERIAL N/A				
APPROVE) IIC		DATE	04/01/09	FINISH N/A	FINISH N/A		
FILE LOC. Q:\Final Release\Specifications						DWG. NO.	1342B-R00	01
SIZE	SCALE	SHT. N	10.	PART NO.				REV
A	NOTED	1 OF	1		1342B-BLK			_





MODEL 1342B-BLK

42" X 72" RECTANGULAR FIBERGLASS BACKBOARD WITH BORDER AND TARGET

The 1342B-BLK backboard shall be molded from fiberglass with a tensile strength of 8,900 to 11,700 PSI and shall have 23% to 27% fiberglass content by weight. All surfaces shall be high gloss white in color with black border and target silk screened on face of bank for permanent markings.

Board goal mounting holes shall be on 5" horizontal and 5" vertical centers and holes on 5" horizontal and 4 ½" vertical centers to accommodate a variety of goals.

Backboard complies with FIBA requirements.

ACCESSORIES

GOALS

Compatible goals are models 726, 5500, 7550, 7555, 140, 240, 39WO, 3942, and 4039. See goal section in specification manual.

Subject to design change and current manufacturing practices. Revised April 4, 2008 ©2008 Gared Holdings, LLC