



| TRUSS HEIGHT FEET & (METERS) | DIM "C" Ft.-In. (Meters) |
|-------------------------------|--------------------------|
| 30.0' TO 31.5' (9.14-9.29M) | 7'-9" (2.37M) |
| 30.6' TO 32.5' (9.30-9.90M) | 7'-9" (2.37M) |
| 32.6' TO 34.5' (9.91-10.51M) | 7'-9" (2.37M) |
| 34.6' TO 36.5' (10.52-11.12M) | 10'-9" (3.28M) |
| 36.6' TO 38.5' (11.13-11.73M) | 10'-9" (3.28M) |
| 38.6' TO 40.0' (11.74-12.19M) | 10'-9" (3.28M) |

DIMENSIONS ABOVE ARE ± 1/2"

NOTE:
STANDARD ATTACHMENT HEIGHTS (TRUSS HEIGHT) FOR MODEL 3204 CLAMPED UNITS ARE 30 FT. MINIMUM AND 40 FT. MAXIMUM. CONTACT PERFORMANCE SPORTS SYSTEMS FOR INFORMATION IF TRUSS HEIGHTS ARE NOT WITHIN THIS RANGE.

| REVISION | | |
|----------|----------|-----|
| REV. | DATE | BY |
| A | 12/08/03 | JJC |
| B | 12/19/06 | WAE |
| C | 05/16/08 | RWP |
| D | 06/05/09 | RWP |
| | | |
| | | |




Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

REAR BRACED REAR FOLD BACKSTOP

| | | | | | |
|---|-----------|----------|----------|-------------|--------------|
| DRAWN | CONNERLEY | DATE | 04/30/03 | MATERIAL | N/A |
| APPROVED | JJC | DATE | 04/30/03 | FINISH | N/A |
| FILE LOC. Q:\Final Release\Specifications | | | | DWG. NO. | 3204 |
| SIZE | SCALE | SHT. NO. | PART NO. | 3204 | |
| A | NONE | 1 OF 1 | | | |
| | | | | | REV D |



MODEL 3204

CLAMPED BENT SINGLE POST REAR BRACED REAR FOLDING BASKETBALL STRUCTURE

RECOMMENDED APPLICATION

This unit is designed for applications allowing sufficient space behind the backboard for the unit to rear fold into a storage position. This single post unit can be used at heights from 30' to 40'.

SPECIFICATIONS

SUPERSTRUCTURE

Unit shall be supported from 3-1/2" O.D. x 0.120" wall ASTM A-500 Grade B horizontal and 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 vertical structural steel tubing secured to the building with heavy gauge steel stampings or weldments (as required by building conditions). When truss span widths exceed 10'-0", 3-1/2" O.D. x Schedule 40 (0.216") wall ASTM A-500 Grade B will be used for the horizontals. Spans over 14'-0" will use welded bridge pipe.

BACKSTOP

The backstop shall be of a single post design with a main vertical mast made of 6-5/8" O.D. x 0.120" wall ASTM A-500 Grade B structural steel tubing bent 30 degrees from vertical with 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tube sway braces clamped in place. Main mast will be suspended from superstructure with a welded steel plate offset hanger 4" in front of the pivot point, less than 4" will not be approved as equal. Backstop shall be manufactured to allow 6" vertical adjustment for plumbing of the backboard. All fittings shall be heavy gauge steel stampings or weldments. A direct goal attachment is used to transfer stress from the goal to the main mast assembly preventing strain on the backboard.

Rear brace shall be 1-7/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tubing attached to the main mast 12" to 18" above the bend in the mast pipe. When brace lengths are than 15'-0", rear brace shall be 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tubing.

Folding brace shall be of a jackknife design with an adjustable hinge for easy installation and field adjustment. Backstop shall be raised and lowered with 1/4" galvanized aircraft cable with a breaking strength of 7000 lbs. Backstop shall be furnished with standard black finish. If special finish coat is required, specify final painting by painting contractor. Backstop manufactured in accordance with 1994 rule 1, section 8, stating that all parts of the backboard support system shall be at least 6" behind backboard.

ACCESSORIES

BACKBOARDS AND GOALS

All PSS and/or Gared backboards and goals are available on this unit. See the backboards and goals section in the specification manual.

BANK PADDING

See the accessories section in the specification manual.

HOISTS

Either Electric hoist or manual winch is available on all folding units. See the accessories section in the specification manual.

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC