





Gared Holdings, LLC 9200 E. 146th St. Noblesville, IN 46060

48" ACRYLIC MULTIPURPOSE BACKBOARD

DRAWN	CONNE	RLEY	DATE	12/02/06	MATERIAL	MATERIAL N/A		
APPROVE	ROVED JJC DATE 12/02/06			FINISH N/A	FINISH N/A			
FILE LOC. Q:\Final Release\Specifications						DWG. NO.	BB48A38	
SIZE	SCALE	SHT.	NO.	PART NO.				REV
Δ	NOTED	1 OF	$\Delta \Delta \Delta \Delta$		Δ			





MODEL BB48A38

STEEL FRAME 48" X 36" RECTANGULAR ACRYLIC BACKBOARD

Backboard shall be constructed of a unitized welded tubular frame utilizing heavy wall ¾" x 1.5" rectangular steel tubing. Frame shall include two vertical struts on 20 inch centers with holes for mounting to support structure. Design shall provide a reinforced goal mounting area to allow for direct mounting of goal, board, and structure. Direct mounting design shall have integral holes to allow permanent attachment of board to post and allow for goal replacement without removing the board.

Backboard shall be designed for use with residential adjustable units, gooseneck posts, and straight arm posts.

Backboard surface shall be constructed of 3/8" thick clear acrylic treated for UV protection, and abrasion resistance. Goal mounting holes shall be on standard 5" horizontal and 5" vertical centers.

Board frame shall be powder coated separately with a flat black weather resistant finish before being assembled.

GOALS

Compatible goals are models 8550, 5500, 8800, 7550, 240, and 39WO. See goal section in specification manual.