



MATERIAL IS 1/2" THICK TEMPERED GLASS WITH STEEL FRAME
 FINISH IS GRAY POWDER COAT ON BRACKETS AND PLATES..

D	JJC	11/22/17
C	RWP	06/08/09
B	WAE	12/18/06
A	JJC	12/01/03
REV	BY	DATE

PSS
PERFORMANCE
SPORTS SYSTEMS

G
GARED™

Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

39" X 54" FAN SHAPED GLASS BACKBOARD

DRAWN CONNERLEY	DATE 5/2/2003	DATE ISSUED
APPROVED	DATE	

FILE LOC. Q:\Inventor Files\Specification Files\07_Backboards

SIZE A	SCALE NONE	SHT. NO. 1 OF 2	PART NO. FSG II	REV D
------------------	---------------	--------------------	---------------------------	-----------------



MODEL FSG II

39"X 54" FAN SHAPED GLASS BACKBOARD

The FSGII backboard shall be fabricated with steel frame constructed of formed steel angles welded together and contoured to match the shape of the glass. Manufacturer of backboard shall have over ten years of experience producing such item.

Key-slots shall be machined into the mounting brackets and spaced at 20" vertical and 35" horizontal to match the standard fan mounting specifications. Entire frame and components shall be powder coated with a durable neutral gray finish. Acrylic cushioning pad shall be used between steel mounting plate and glass to protect board against possible breakage.

Glass shall be ½" in thickness and is fully tempered with the white target lines permanently fused onto the surface. 12mm glass will not be considered equal to ½" glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full ½" glass. Vinyl shock absorbing material shall insulate the glass from the frame. Goal mounting holes shall be on 5" horizontal and 5" vertical centers.

ACCESSORIES

GOALS

Compatible goals are models 1000, 2000+, and 5500. See goal section in specification manual.

Subject to design change and current manufacturing practices.